


상세보기


[FullText Download](#)
[마이플러저장](#)
[마이플러보기](#)

JP 02657184

(54) HYDRAULIC AUTO-BALANCER

- (19) 국가 (Country) : JP (Japan)
- (11) 공개번호 (Publication Number) : 1989-301061 (1989.12.05) [▶ 日本語/한글\(JP\)](#)
[▶ 현재진행상태보기](#)
- (13) 문헌종류 (Kind of Document) : A (Unexamined Publication)
- (21) 출원번호 (Application Number) : 1988-131066 (1988.05.28)
- (75) 발명자 (Inventor) : NAGASE NOBORU, YAMAGUCHI MASAO, NOGUCHI NORITAKA, ITAT
- (73) 출원인 (Assignee) : NAGASE IRON WORKS CO LTD.
- (57) 요약 (Abstract) :

PURPOSE: To eliminate any residue in a pocket forcibly as well balancing work performable by setting up a liquid injection nozzle specific phasic pocket and correcting any unbalance in a rotor, an exhausting the liquid in the pocket to the outside, respectively.

CONSTITUTION: An air passage in a selector valve 17 and a gas- opened, and pressurized air A is put into a full pocket 10 of a rotor (from this nozzle 3 via a filler hole 13, and with this pressure, a liq behind in the pocket 10 are exhausted to the outside. Next, a liquid 17 and the gas-liquid injection nozzle 3 are opened, and the liqu pocket 10 from the nozzle 3 via the filler hole 13 of a balancing ring 2 with centrifugal force with rotation of the rotor 9. With this constituti of weight acts on the specified phase of the rotor 9, so that any automatically corrected.

COPYRIGHT: (C)1989,JPO&JPIO

대표도면